

Safety Data Sheet

according to UK REACH Regulation

OLI-AQUA DOMO 15.40

Revision date: 05.11.2025

Product code: A00728

Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

OLI-AQUA DOMO 15.40

Further trade names

OLI-AQUA DOMO
Parkettsiegel 15.40
diverse Glanzgrade

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Colour

1.3. Details of the supplier of the safety data sheet

Company name:	Oli Lacke GmbH	
Street:	Bahnhofstrasse 22	
Place:	D-09244 Lichtenau	
Telephone:	+49 37208 84200	Telefax: +49 37208 84268
e-mail:	info@oli-lacke.de	
Contact person:	Gemeins.	Telephone: +49(0)361/730730
	Gifinformationszentrum Erfurt	
Internet:	www.oli-lacke.de	

1.4. Emergency telephone number: Gemeins. Gifinformationszentrum Erfurt
+49(0)361/730730

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****GB CLP Regulation**

This mixture is not classified as hazardous in accordance with GB CLP Regulation.

2.2. Label elements**GB CLP Regulation****Precautionary statements**

P102 Keep out of reach of children.

Special labelling of certain mixtures

EUH208 Contains 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one, reaction mass of 5
-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce
an allergic reaction.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

Safety Data Sheet

according to UK REACH Regulation

OLI-AQUA DOMO 15.40

Revision date: 05.11.2025

Product code: A00728

Page 2 of 8

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
112-34-5	2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether			1 - < 5 %
	203-961-6	603-096-00-8	01-2119475104-44	
	Eye Irrit. 2; H319			
2634-33-5	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one			< 0.1 %
	220-120-9	613-088-00-6		
	Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Skin Sens. 1, Aquatic Acute 1; H302 H315 H318 H317 H400			
55965-84-9	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)			< 0.1 %
	-	613-167-00-5		
	Acute Tox. 2, Acute Tox. 2, Acute Tox. 3, Skin Corr. 1C, Eye Dam. 1, Skin Sens. 1A, Aquatic Acute 1, Aquatic Chronic 1; H330 H310 H301 H314 H318 H317 H400 H410 EUH071			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
112-34-5	203-961-6	2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether	1 - < 5 %
	dermal: LD50 = 4120 mg/kg; oral: LD50 = 5660 mg/kg		
2634-33-5	220-120-9	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one	< 0.1 %
	oral: ATE = 500 mg/kg Skin Sens. 1; H317: >= 0,05 - 100		
55965-84-9	-	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	< 0.1 %
	inhalation: ATE = 0,5 mg/l (vapours); inhalation: ATE = 0,05 mg/l (dusts or mists); dermal: ATE = 50 mg/kg; oral: ATE = 100 mg/kg Skin Corr. 1C; H314: >= 0,6 - 100 Skin Irrit. 2; H315: >= 0,06 - < 0,6 Eye Dam. 1; H318: >= 0,6 - 100 Eye Irrit. 2; H319: >= 0,06 - < 0,6 Skin Sens. 1A; H317: >= 0,0015 - 100 M acute; H400: M=100 M chron.; H410: M=100		

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

When in doubt or if symptoms are observed, get medical advice.

Never give anything by mouth to an unconscious person or a person with cramps.

If unconscious but breathing normally, place in recovery position and seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest.

If breathing is irregular or stopped, administer artificial respiration.

After contact with skin

Immediately remove any contaminated clothing, shoes or stockings.

After contact with skin, wash immediately with plenty of water and soap.

Do not wash with: Solvents/Thinner

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

Seek medical advice immediately.

Safety Data Sheet

according to UK REACH Regulation

OLI-AQUA DOMO 15.40

Revision date: 05.11.2025

Product code: A00728

Page 3 of 8

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).
Call a physician immediately.
Put victim at rest, cover with a blanket and keep warm.
Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Impaired consciousness

4.3. Indication of any immediate medical attention and special treatment needed

Call a physician immediately.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

alcohol resistant foam, Carbon dioxide (CO₂), Extinguishing powder, Water mist

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke.
Hazardous decomposition products: carbon black. Danger of serious damage to health by prolonged exposure.
Use appropriate respiratory protection.

5.3. Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers.
Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Contains: Solvent - Keep away from sources of ignition - No smoking. Ventilate affected area.
Avoid breathing dust/fume/gas/mist/vapours/spray.
Safe handling: see section 7
Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up**Other information**

Prevent spread over a wide area (e.g. by containment or oil barriers). Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).
Collect in closed and suitable containers for disposal. Disposal: see section 13
Clean with detergents. Avoid solvent cleaners.

6.4. Reference to other sections

See section 8.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Contains: Solvent - In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. Only use the material in places where open light, fire and other flammable sources can be kept away. Use explosion-proof electrical equipment.

Safety Data Sheet

according to UK REACH Regulation

OLI-AQUA DOMO 15.40

Revision date: 05.11.2025

Product code: A00728

Page 4 of 8

Never use pressure to empty container. Keep/Store only in original container. Do not allow to enter into surface water or drains. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

Avoid contact with skin, eyes and clothes. Avoid: Inhalation of vapours or spray/mists, Inhalation of dust/particles. When using do not eat, drink or smoke.

Advice on protection against fire and explosion

Solvent - Vapours are heavier than air, spread along floors and form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Store in accordance with: Betriebssicherheitsverordnung (BetrSichV)

Hints on joint storage

Do not store together with: Oxidising agent, Strong acid, Strong alkali

Further information on storage conditions

Follow the instructions for use on the label.

storage temperature of °C 5 up to °C 30

Contains: Solvent - Keep container tightly closed in a cool, well-ventilated place. Protect from sunlight. Keep away from sources of ignition - No smoking. Store in a place accessible by authorized persons only. Always close containers tightly after the removal of product.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
112-34-5	2-(2-Butoxyethoxy)ethanol	10	67.5		TWA (8 h)	WEL
		15	101.2		STEL (15 min)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL

8.2. Exposure controls**Appropriate engineering controls**

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Wear eye/face protection.

Hand protection

Wear suitable gloves. Replace when worn. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. See information supplied by the manufacturer.

Suitable material: NBR (Nitrile rubber).

Use protective skin cream before handling the product.

Skin protection

Wear anti-static footwear and clothing (Natural fibres (e.g. cotton) / heat-resistant synthetic fibres)

Safety Data Sheet

according to UK REACH Regulation

OLI-AQUA DOMO 15.40

Revision date: 05.11.2025

Product code: A00728

Page 5 of 8

Respiratory protection

Respiratory protection necessary at: exceeding exposure limit values.
Use suitable breathing apparatus.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state: liquid
Colour:

Test method**Changes in the physical state**

Boiling point or initial boiling point and boiling range:	100 °C
Flash point:	> 60 °C DIN EN ISO 1523
Lower explosion limits:	1,4 vol. %
Upper explosion limits:	10,4 vol. %
Auto-ignition temperature:	240 °C
pH-Value (at 20 °C):	7- 9
Flow time: (at 20 °C)	verarbeitungsfertig
Vapour pressure: (at 20 °C)	31,6 hPa
Density (at 20 °C):	1,01 g/cm ³ ISO 2811

9.2. Other information**Other safety characteristics**

Solvent separation test:	< 3 %
Solvent content:	3,5 %
Solid content:	30 %

Further Information**SECTION 10: Stability and reactivity****10.1. Reactivity**

refer to chapter 7. No further action is necessary.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Exothermic reaction with: Oxidising agent, Strong acid, Strong alkali

10.4. Conditions to avoid

In case of warming: Formation of: Hazardous decomposition products

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products

Nitrogen oxides (NO_x), carbon black, Carbon dioxide (CO₂), Carbon monoxide

Safety Data Sheet

according to UK REACH Regulation

OLI-AQUA DOMO 15.40

Revision date: 05.11.2025

Product code: A00728

Page 6 of 8

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in GB CLP Regulation****Acute toxicity**

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
112-34-5	2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether				
	oral	LD50 mg/kg	5660	Rat	
	dermal	LD50 mg/kg	4120	Rabbit	
2634-33-5	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one				
	oral	ATE mg/kg	500		
55965-84-9	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)				
	oral	ATE mg/kg	100		
	dermal	ATE	50 mg/kg		
	inhalation vapour	ATE	0,5 mg/l		
	inhalation dust/mist	ATE	0,05 mg/l		

Further information

There are no data available on the mixture itself.

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

Reference to other sections: 2, 3

SECTION 12: Ecological information**12.1. Toxicity**

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
112-34-5	2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether					
	Acute algae toxicity	ErC50 mg/l	> 100	Scenedesmus sp.		
	Acute crustacea toxicity	EC50 mg/l	> 100	48 h Daphnia magna		

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
112-34-5	2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether	0,56 (25°C)

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

Safety Data Sheet

according to UK REACH Regulation

OLI-AQUA DOMO 15.40

Revision date: 05.11.2025

Product code: A00728

Page 7 of 8

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

Further information

There are no data available on the mixture itself.
Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains.
Dispose according to legislation.

List of Wastes Code - residues/unused products

080112 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish other than those mentioned in 08 01 11

List of Wastes Code - used product

080112 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish other than those mentioned in 08 01 11

List of Wastes Code - contaminated packaging

080112 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish other than those mentioned in 08 01 11

Contaminated packaging

Completely emptied packages can be recycled.
Dispose according to legislation.

SECTION 14: Transport information**Land transport (ADR/RID)****Other applicable information (land transport)**

No dangerous good in sense of these transport regulations.

Inland waterways transport (ADN)**Other applicable information (inland waterways transport)**

No dangerous good in sense of these transport regulations.

Marine transport (IMDG)**Other applicable information (marine transport)**

No dangerous good in sense of these transport regulations.

Air transport (ICAO-TI/IATA-DGR)**Other applicable information (air transport)**

No dangerous good in sense of these transport regulations.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

Safety Data Sheet

according to UK REACH Regulation

OLI-AQUA DOMO 15.40

Revision date: 05.11.2025

Product code: A00728

Page 8 of 8

14.6. Special precautions for user

refer to chapter 7. No further action is necessary.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 55, Entry 75

2010/75/EU (VOC): 35 g/l

National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

Additional information

Observe in addition any national regulations!

15.2. Chemical safety assessment

For this substance a chemical safety assessment is not required.

SECTION 16: Other information**Relevant H and EUH statements (number and full text)**

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.
EUH208	Contains 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)