



SCAN QR CODE
for datasheets, safety
information – available in
multiple languages



TECHNICAL DATA SHEET

OLI Parquet Care

MATT | GLOSS 15.95

(formerly OLI-AQUA POLISH)

Water-based polymer dispersion for initial care and refreshing of water-resistant sealed parquet, wood and cork floors. Protects against abrasion, scuff marks and scratches, ensures a well-maintained appearance, helps preserve value and extends the service life of the sealant. For residential, commercial and sports floors in accordance with DIN 18032. Available in matt and, from 08/2026, also in gloss.

Gloss level	Packaging	Item no.	Pack	Item no. Packing
Matt 15.95	1 L	A00698_TD	4 x 1 L	A00698_TD_VE4
	2.5 L	A00698_RG	2 x 2.5 L	A00698_RG_VE2
*Glossy 15.95	1 L	A00697_TD	4 x 1 L	A00697_TD_VE4
	2.5 L	A00697_RG	2 x 2.5 L	A00697_RG_VE2

* Available from August 2026.

Area of application

- Interior wood
- Lacquered or waterproof-sealed parquet and cork floors, as well as wooden stairs
- Factory-UV-sealed pre-finished parquet
- Residential and commercial use
- Suitable for sealed sports floors in accordance with DIN 18032.

Properties

- Polymer care product for initial care and refreshing of sealed parquet, wood and cork surfaces
- Forms a protective care film to preserve the sealant
- Protects against scuff marks, scratches and wear
- Facilitates regular cleaning
- Visibly refreshes the surface
- Recommended after every deep clean
- Part of the coordinated care and cleaning system with OLI Parquet Cleaner 15.94

Complies with/Tested to

- Giscode GE10
- Suitable for sports floors in accordance with DIN 18032

Notes

- Shake well before use.
- Avoid direct sunlight and draughts.
- Do not leave parquet and wooden floors damp or wet for prolonged periods.

- Switch off underfloor heating in good time before use.
- Optimal application temperature is approx. +20 °C.
- Do not apply when the floor or material temperature is below +15 °C.

Application

Preparation

- Clean the surface thoroughly and allow to dry completely.
- We recommend pre-cleaning with OLI Parquet Cleaner 15.94.

Application

- Shake the container well before use.
- Apply the care product undiluted with a mop in a thin, even layer.
- Leave to dry for at least 12 hours.
- Do not polish.

Tip

- For increased protection, repeat the application as soon as the care film is touch-dry.

Technical data

Binder base	Polymer dispersion
Gloss level	Matt (15.95) / Gloss (15.95) (from 08/2026)
Coverage	approx. 25–30 g/m ² per coat
Coverage	approx. 30–40 m ² /L per coat
Tools	Mop
Cleaning tools	Immediately after use with water
Disposal	Containers and residues in accordance with local regulations
System products	Parquet Cleaner 15.94, Intensive Cleaner 15.97
Shelf life	24 months in the original sealed container. Store in a cool, dry, frost-free place; not below +5 °C and not above +30 °C.
Safety	Regulation (EC) No 1272/2008 (CLP) Not subject to labelling requirements. P102 Keep out of reach of children. EUH208 Contains a reaction mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May cause an allergic reaction. Further safety instructions and labelling in accordance with the current safety data sheet.

Our technical recommendations, whether verbal or written, are provided for guidance only and are not binding. They are based on our experience and the current state of knowledge from practical application. They do not relieve the user of the responsibility to test our products themselves to ensure their suitability for the intended use. All previous editions are hereby superseded. Date: 13 June 2026_GS_V1