



SCAN QR CODE  
for datasheets, safety info – multilingual  
available



TECHNICAL DATA SHEET

# OLI-NATURA Refresher

**HYDRO CARE OIL FOR OILED WOODEN SURFACES. CARES FOR PARQUET – STAIRS – FURNITURE NEUTRAL IN APPEARANCE, VOC-FREE, ENVIRONMENTALLY FRIENDLY & LOW ODOUR**

VOC-free hydro care oil for initial care and refreshing of all oxidatively oiled wood surfaces indoors – especially for light-coloured, white or OLI-NATURA Scandic Oil-treated surfaces with a raw wood effect. The neutral oil does not change the colour of the wood, has a mild odour and can be easily applied without streaks using a cloth, pad, flat mop or sprayer.

Colour	Item	Container / PU	Palette
Neutral (pigment-free)	A04429_KF	1 x 5 L	96
Neutral (pigment-free)	A04429_KF_V2	2 x 5 L	48
Neutral (pigment-free)	A04429_EL	1 x 1 L	288
Neutral (pigment-free)	A04429_EL_V4	4 x 1 L	72
Neutral (pigment-free)	A04429_EK	1 x 250 ml	
Neutral (pigment-free)	A04429_EK_V24	24 x 250 ml	

*\* Large containers and bulk containers available on request.*

<b>Area of application</b>	<ul style="list-style-type: none"> <li>▪ Indoor wood</li> <li>▪ Private &amp; commercial</li> <li>▪ Solid wood parquet &amp; floorboards</li> <li>▪ Furniture &amp; stairs</li> </ul>
<b>Properties</b>	<ul style="list-style-type: none"> <li>▪ Nourishes &amp; regenerates, restores protection to pre-oiled surfaces</li> <li>▪ Does not alter the appearance of pre-oiled surfaces</li> <li>▪ Pleasant odour, VOC-free, no risk of spontaneous combustion</li> <li>▪ Easy to apply with a cotton cloth, mop or sprayer</li> <li>▪ High yield: 1 litre is sufficient for approx. 40 m<sup>2</sup> per coat</li> <li>▪ Giscode Ö10+, solvent-free, healthy for living, suitable for children's toys (DIN EN 71-3)</li> </ul>
<b>Complies with/tested according to</b>	<ul style="list-style-type: none"> <li>▪ Giscode Ö10</li> <li>▪ DIBT-tested building product</li> <li>▪ baubook declared</li> <li>▪ DIN 71-3 (safety of children's toys)</li> <li>▪ DIN 53160 (saliva and sweat resistant)</li> <li>▪ Cobalt-free &amp; oxime-free, FREE from formaldehyde,</li> <li>▪ aromatics, biocides, free from formaldehyde, aromatics, biocides, cobalt and oximes</li> </ul>
<b>Notes</b>	<ul style="list-style-type: none"> <li>▪ Material, object and ambient temperature +15 to +30 °C.</li> </ul>

- Shake the container well before use, as the raw materials may separate.
- Remove excess material from the surface, avoid puddles.
- Carry out a preliminary test on exotic woods rich in constituents.
- Oxidative drying: Ensure windows are open and air can circulate during and after application.
- No risk of spontaneous combustion!

#### Preparation

Before any maintenance work, we recommend dry cleaning and damp cleaning with OLI-NATURA wood soap. Allow the surface to dry completely.

#### Application

##### Refreshing large areas:

- Apply Refresher sparingly and evenly with a sprayer (pressure sprayer) and then spread with a mop or flat mop.
- Use Refresher pure and undiluted.
- Work in sections and in slightly overlapping strips.
- Simply allow Refresher to dry.

##### Refreshing small areas:

- Soak a white pad or oil-absorbent cloth/cotton cloth with Refresher and rub it gently into the wood.
- Use Refresher undiluted and unmixed.
- Remove excess oil with an oil-absorbent cloth or cotton cloth.
- Simply allow Refresher to dry.

**Consumption:** 1 coat, approx. 20-30 g/m<sup>2</sup> (approx. 35-50 m<sup>2</sup>/l), depending on the absorbency of the wood. The application quantities vary and depend heavily on how "leached" the surface was.

**Drying:** Depending on humidity/temperature, the surface can be walked on after 2 hours and can be used after drying overnight. Do not wipe with a damp cloth in the first few days. Do not clean with a damp cloth or treat with care in the first 5-7 days while the oil is still hardening.

#### Technical data

<b>Solid content:</b>	Low
<b>VOC:</b>	-
<b>Wood emphasis:</b>	Low - neutral
<b>Colours:</b>	Natural
<b>Hardener:</b>	-
<b>Coats:</b>	1 x with approx. 20-30 g/m <sup>2</sup> (1 litre approx. 35-50 m <sup>2</sup> per application)
<b>Application method:</b>	Sprayer, squeegee, flat mop, cotton cloth or white pad
<b>Cleaning of tools:</b>	Rinse tools with water immediately after use. Dispose of cleaning residues properly.
<b>Shelf life:</b>	At least 24 months in original sealed container. Store in a cool, dry place protected from frost. Opened containers: Seal immediately and use promptly.
<b>Disposal:</b>	Empty containers and product residues must be disposed of in accordance with regional regulations.
<b>Declaration:</b>	Modified vegetable oils, linseed oil, wood oil, castor oil, lead- and cobalt-free dryer, oxime-free anti-skin agent.
<b>Safety:</b>	No labelling required, not a hazardous material. P102 Keep out of reach of children. Further safety information can be found in the safety data sheet at <a href="http://www.oli-lacke.de">www.oli-lacke.de</a> .

---

Our written and verbal recommendations for application are for guidance only. They are based on our experience and current knowledge from practical use. They do not release the user from their responsibility to test our products for their suitability for the intended use. All previous editions are hereby invalidated. Status: 18.11.24\_GS\_UPD 11092025\_sst

---