



TECHNICAL DATA SHEET

OLI-NATURA PreOilCleaner

Cleaning pre-treatment for all wooden surfaces

PreOilCleaner cleans thoroughly and ensures optimal pre-treatment of untreated or freshly sanded wooden surfaces such as furniture, stairs, parquet and panelling. It increases the wood's absorbency and minimises tannin reactions in tannin-rich woods such as oak. Suitable for all types of wood, it is diluted with water and applied before oiling.

Item No. A05403

Range

Qty. per pallet	288	72		
Quantity per pack	1 x 1 L	4 x 1 L	1 x 250 ml	6 x 250 ml

Area of application

- Pre-treatment of all wooden surfaces prior to oil finishing

Properties

- Prepares the surface perfectly for an oil finish
- Increases oil absorption, intensifies the colour of coloured oils and reduces the risk of water marks and tannin stains
- Diluted in a ratio of 1:4 with lukewarm water

Complies with/Tested to

- EU Decopaint compliant
- Free from formaldehyde, aromatic compounds, biocides, preservatives, cobalt and oximes
- Giscode: GG20

Notes

Material, surface and ambient temperature +15 to +30 °C. Shake or stir well before use!

This product is NOT suitable for regular, daily cleaning.

When using the OLI-NATURA Antique reactive stain, the surface should NOT be treated with PreOilCleaner beforehand.

Pre-treatment with PreOilCleaner may cause the wood to become slightly rough. Intermediate sanding will remedy this.

Wood preparation

Sand the wood surface professionally. Final sanding for furniture: P180–240; final sanding for floors: 100–150

The coarser the sanding, the more rustic the effect.

The finer the sanding, the more even the effect. Wood moisture content 8–12%

Dust thoroughly

Application

- 1) Thoroughly remove dust from the surface.
- 2) Shake the bottle well and mix with lukewarm water in a ratio of 1:4.
- 3) Lightly dampen a cloth, sponge or cotton ball and apply to the surface evenly until it is damp to the touch, without leaving puddles. For heavily

stains, the treatment can be repeated.

- 4) Allow the wooden surface to dry thoroughly until it looks and feels uniformly dry. Depending on the size of the area, this may take 2–8 hours; for larger areas such as parquet floors, it may take longer.
- 5) Intermediate sanding: Once dry, if necessary, lightly sand with a fine-grit sandpaper in the direction of the grain, as the wood may become slightly rough. Dust thoroughly.
- 6) The wood surface is then thoroughly dusted and treated with a protective OLI-NATURA oil of your choice.

Drying: Allow to dry completely (2–8 hours, depending on conditions and the size of the area). Once dry, smooth with a fine-grit sandpaper if necessary, as the wood may have become slightly rough.

Tips:

- This product is NOT intended for regular, daily cleaning.
- When using the “Antique” reactive stain, do NOT pre-treat the surface with Pre-Treat beforehand.

Technical data	Solid content:	-
	VOC:	163 g/l
	Tinting:	-
	Colours:	-
	Hardener:	-
	Coats:	At least 1 coat
	Mixing ratio:	1:4 with water
	Application method:	Sponge, mop, cotton pad, cloth
	Cleaning of tools:	Water
	Shelf life:	Unopened: min. 24 months. Protect from frost.
	Disposal:	Empty containers and product residues must be disposed of in accordance with local regulations.
	Declaration:	
	Safety	No labelling required, not a hazardous substance. Further safety instructions can be found in the safety data sheet at www.oli-lacke.de .

Our written and verbal recommendations regarding product application are provided for guidance only and are not binding. They are based on our experience and the current state of knowledge gained from practical application. They do not relieve the applicator of the responsibility to test our products themselves to ensure they are suitable for the intended purpose. All previous editions are hereby superseded. Date: 17 October 2024_sst
